

PMTi10B2-03

Power Strip with 20x IEC C13 + 3x IEC C19 Outlets, 2RU Horizontal



Key Features

- 10 x 10A C13 IEC outlets (C19, 3 Pin and hardwired outlets also available)
- 240 VAC – 50 Hz, 16A total current loading
- Automatic Transfer Switch – with manual switch override. Rated up to 63A.
- Indicator lights show which feed is active
- Auto-reconnect prioritises the A power feed, to stay connected whenever this feed is live.
- Available with total current loading up to 32A, with optional C Curve or D Curve Circuit Breaker.
- Plugs - a range of options can be fitted as required.
- Lead Length - 3m standard, other lengths available as required.
- Optional LCD current meter.
- Front or rear cable entry available.
- Manufactured from 1.2mm mild steel.
- Finished in black satin ripple powder-coat, with other colours/finish available to order.
- Manufactured to comply with AS/NZS 3100:2022
- New Zealand Designed & Manufactured



NZ Manufacturer
High Quality Products –
Made to Last



5-year warranty
On Manufactured Items



Flexibility
Low MOQ's



Engineered Solutions
Custom power solutions

Specifications

Product Code	PMTi10B2-03
Mounting Style	2RU Horizontal Mounted
Current Rating	16A Single Phase
Voltage Rating	220V AC ±10%
Frequency	50/60Hz
Input	2x 1.5m input lead to IEC C20 Plug, 16 Amp 1.5mm ² conductor wire
Outlets	10 x 10 Amp IEC C13 outlets
Dimensions (WxHxD)	483 x 88 x 64mm
Weight	3.2kg
Temperature	0 – 40°C
ATS Changeover Time	<50ms
Mechanical Life (ATS Switch)	>8000 times
Protection	63Amp overload protection
Rated Short Circuit Current Limit	16A
Regulatory Standards	AS/NZS 3100:2022, IEC60947-6



NZ Manufacturer
High Quality Products –
Made to Last



5-year warranty
On Manufactured Items



Flexibility
Low MOQ's



Engineered Solutions
Custom power solutions